



s1

MANGER
PRECISION IN SOUND



REALITY FEELS AT HOME

The Manger s1 is a classic redefined. We threw in all of our knowledge from the past 45 years, enhanced it with only the best materials and produced it under the highest possible level of precision.

Inspired by your individual taste

The accurate, innovative and authentic s1 has quickly become our flagship system. A classic and smooth design, excellent production quality and unparalleled audio reproduction.

Affectionate design meets ultimate function

A pure body. Ultra sleek look and feel with a high end finish of your choice. Smooth and round corners not only make you feel attracted to the s1 - first and foremost they enhance the circulation of the audio waves.

Driven by the Manger Sound Transducer

Our patented, ultrafast sound transducer accurately reproduces subtle musical structures, while the built-in woofers generate even the lowest octaves with ease.

Fortitude from top to bottom

Four spikes guarantee a firm stand, giving the 105.7 lbs (48 kg) heavy active system the stability and precision it needs during every performance.

General

Type	Active 2-Way Floorstanding System
Frequency Range	30 Hz – 40 kHz
Crossover frequency	330 Hz
Maximum SPL	110 dB Peak
Dimensions (H x W x D)	44.8 x 10.6 x 8.4" (1139 x 270 x 214 mm)
Weight	105.7 lbs (48 kg)

Chassis

HF	Manger® Sound Transducer, Bandwidth 80 Hz – 40 kHz, Rise Time 13 µs
LF	8" (200 mm) Glass Fiber-Polyester Sandwich Design, 38 mm Voice Coil Diameter
Enclosure	closed

Amplifiers

Max. Power Output LF	250 W @ 8 Ohms Class AB
Max. Power Output HF	180 W @ 8 Ohms Class AB
Power Bandwidth HF	250 kHz (-3 dB)
Input Sensitivity	6 dBu (1.55 V) or 0 dBu
Input Impedance	10 kOhms
Input	XLR-3 (balanced)

Various

Control Switches	Individual Adjustment Options
Power LED • Limiter LED	green • green/red
Finish	silk matt as per RAL, Nextel, veneer or UltraHigh Gloss

Selection



RAL 9010 RAL 9022 RAL 3004 Makassar Ebony Santos Palisander

your partner