exaudio
a arte do som

LUMIN

Tabela de Preços - Abril 2026

PVP recomendado IVA a 23% incluido.

Modelo **Preço Final**

Network Music Players

D3 — 2.890,00 €

DSD Support: Up to DSD256, 1-bit, Stereo
PCM Support: Up to 384kHz, 16–32-bit, Stereo
Analog Output Stage: ESS SABRE32 ES9028Pro DAC chip
Balanced layout with high-quality components
Upsampling rates & bit depths: DSD256 upsampling option for all files
PCM 384kHz upsampling option for all files
Digital Output Stage: BNC SPDIF: PCM 44.1kHz–192kHz, 16–24-bit
DSD (DoP, DSD over PCM) 2.8MHz, 1-bit
Dimensions: 300mm (W), 244mm (D), 60mm (H), 2.5kg
aluminio anodizado / preto anodizado

T3X — 5.990,00 €

DSD Support: Up to DSD256, 1-bit, Stereo
PCM Support: Up to 384kHz, 16–32-bit, Stereo
Analog Output Stage: Dual ESS SABRE32 ES9028Pro DAC chips
Balanced layout with high-quality components
Upsampling rates & bit depths: DSD256 upsampling option for all files
PCM 384kHz upsampling option for all files
Digital Output Stage: BNC SPDIF: PCM 44.1kHz–192kHz, 16–24-bit
DSD (DoP, DSD over PCM) 2.8MHz, 1-bit
Dimensions: 350mm (W), 350mm (D), 60.5mm (H), 6kg
aluminio anodizado / preto anodizado

João Pina Unipessoal Lda. Rua de Braga, Lt.1, Lj. Esq. 2755-275 Alcabideche
T: 21 4649110 E: geral@exaudio.net W: www.exaudio.net

exaudio
a arte do som

LUMIN

X2 — 17.390,00 €

DSD Support: Up to DSD256, 1-bit, Stereo
PCM Support: Up to 384kHz, 16–32-bit, Stereo
Analog Output Stage: LUMIN Discrete DAC chips Balanced layout with high-quality components
Upsampling rates & bit depths: DSD256 upsampling option for all files
PCM 384kHz upsampling option for all files
Digital Output Stage: BNC SPDIF: PCM 44.1kHz–192kHz, 16–24-bit
DSD (DoP, DSD over PCM) 2.8MHz, 1-bit
Feet IsoAcoustics isolating feet on main chassis
Lumin (solid aluminium chassis): 350mm (W), 345mm (D), 77mm (H), 8kg
PSU (solid aluminium chassis): 106mm (W), 334mm (D), 77mm (H), 4kg
aluminio anodizado / preto anodizado

Network Transports

U2 mini — 2.690,00 €

Network playback: Up to DSD512, Up to 768kHz, 16–32-bit, Stereo, MQA decoding
Upsampling rates & bit depths: DSD256 upsampling option for all files
PCM 384kHz upsampling option for all files
Digital Output Stage: USB: Native DSD512 support PCM 44.1–768kHz, 16–32-bit, Stereo

Optical, Coaxial RCA, Coaxial BNC & AES/EBU: DSD64 (DoP64, DSD over PCM) PCM 44.1kHz–192kHz, 16–24-bit
Dimensions: 300mm (W), 244mm (D), 60mm (H), 2.5kg
aluminio anodizado / preto anodizado

U2 — 5.499,00 €

Network playback: Up to DSD512, Up to 768kHz, 16–32-bit, Stereo, MQA decoding
Upsampling rates & bit depths: DSD256 upsampling option for all files
PCM 384kHz upsampling option for all files
Digital Output Stage: USB: Native DSD512 support PCM 44.1–768kHz, 16–32-bit, Stereo

Optical, Coaxial RCA, Coaxial BNC & AES/EBU: DSD64 (DoP64, DSD over PCM) PCM 44.1kHz–192kHz, 16–24-bit
Dimensions: 350mm (W), 350mm (D), 60.5mm (H), 6kg
aluminio anodizado / preto anodizado

exaudio
a arte do som

LUMIN

U2X — 11.990,00 €

Network playback: Up to DSD512, Up to 768kHz, 16–32-bit, Stereo, MQA decoding
Upsampling rates & bit depths: DSD256 upsampling option for all files
PCM 384kHz upsampling option for all files
Digital Output Stage: USB: Native DSD512 support PCM 44.1–768kHz, 16–32-bit, Stereo

Optical, Coaxial RCA, Coaxial BNC & AES/EBU: DSD64 (DoP64, DSD over PCM) PCM 44.1kHz–192kHz, 16–24-bit
Feet IsoAcoustics isolating feet on main chassis
Lumin (solid aluminium chassis): 350mm (W), 345mm (D), 77mm (H), 8kg
PSU (solid aluminium chassis): 106mm (W), 334mm (D), 77mm (H), 4kg

P1 mini — 5.490,00 €

Streamer - DAC - Pré-amplificador
DSD Support: Up to DSD256, 1-bit, Stereo
PCM Support: Up to 384kHz, 16–32-bit, Stereo
Analog Output Stage: ESS SABRE32 ES9028Pro DAC chip
Balanced layout with high-quality components
Upsampling rates & bit depths: DSD256 upsampling option for all files
PCM 384kHz upsampling option for all files
Digital Output Stage: BNC SPDIF: PCM 44.1kHz–192kHz, 16–24-bit
DSD (DoP, DSD over PCM) 2.8MHz, 1-bit
HDMI:(HDMI Passthrough and ARC support), PCM 2.0 Audio support, 4K Video Passthrough, ARC (Audio Return Channel) support
Dimensions: 400mm (W), 314mm (D), 77mm (H), 7kg
aluminio anodizado / preto anodizado

exaudio
a arte do som

LUMIN

P2 — 14.290,00 €

Streamer - DAC - Pré-amplificador
9 digital & analogue inputs
DSD Support: Up to DSD256, 1-bit, Stereo
PCM Support: Up to 384kHz, 16–32-bit, Stereo

Analog Output Stage: Dual ES9038PRO SABRE DACs in Mono mode, Balanced layout with high-quality components

Upsampling rates & bit depths: DSD256 upsampling option for all files
PCM 384kHz upsampling option for all files
Digital Output Stage: BNC SPDIF: PCM 44.1kHz–192kHz, 16–24-bit
DSD (DoP, DSD over PCM) 2.8MHz, 1-bit
HDMI:(HDMI Passthrough and ARC support), PCM 2.0 Audio support, 4K Video Passthrough, ARC (Audio Return Channel) support
Dimensions: 350mm (W), 380mm (D), 107mm (H), 12kg
aluminio anodizado / preto anodizado

Power Amp. — 14.290,00 €

Operating Mode: (selectable) Stereo, Dual Mono or Bridged mode
Input: (selectable) 1 x XLR pair (pin 2 hot), 1 x RCA pair
Power: 160W per channel into 8Ω, 320W per channel into 4Ω, 640W into 8Ω (Bric
Frequency Response: 20hz - 40000hz ± 0.1db
Gain: +26dB (Stereo, Dual Mono), +32dB (Bridged)
Dimensions: 350mm (W), 374mm (D), 104mm (H), 19Kg

L2 — 3.520,00 €

Internal Storage:
No drives, 4TB (2x 2TB) or 8TB (2x 4TB) 2.5" SSD — SSD 4TB **4.690,00 €**
Connections:
USB 3.0 Micro Type B Slave for connection to computer*
2x Gigabit Ethernet Network (1000BASE-T) RJ45 — SSD 8TB **5.790,00 €**
2x Industry-standard Gigabit SFP
Dimensions: 350mm (W), 350mm (D), 60.5mm (H), 6kg

Telecomando — 345,00 €

por infravermelhos para ligar a porta usb